AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

- (original) A method for producing a layer-like part
 in which
- the part (16) is created on a substrate (12) by coating of the substrate (12), the substrate (12) consisting of a shape memory alloy,
- the substrate (12) coated with the part (16) is subjected to temperature control in such a way that the substrate undergoes a change in shape on account of the shape memory effect
- and the part (16) is separated from the substrate band
 (12),

characterized in that the microstructure texture of the substrate band is transferred to the layer-like part by the latter undergoing quasi-epitaxial growth.

2. (original) The method as claimed in claim 1, characterized in that, in the case of the substrate (12), the one-way effect is used by the substrate being deformed before coating and heated after coating in such a way that the substrate goes over into its undeformed shape.

- 3. (original) The method as claimed in claim 1, characterized in that, in the case of the substrate (12), the two-way effect is used by the substrate being subjected to temperature control before coating in such a way that it goes over into its one shape and the substrate being subjected to temperature control after coating in such a way that it goes over into its other shape.
- 4. (original) The method as claimed in claim 3, characterized in that the substrate (12) is alternately heated and cooled after coating in such a way that it alternately goes over into its one shape and its other shape.
- 5. (withdrawn) A production facility with a substrate band (12) for producing a layer-like part (16) in sheet form, the substrate band (12) being led through a creating device (17) for the part and a temperature-controllable separating device (15) to obtain the part, and the substrate band consisting of a shape memory alloy, characterized in that the creating device is intended for quasi-epitaxial growth of the layer-like part onto the substrate band.

- 6. (withdrawn) The production facility as claimed in claim 5, characterized in that the creating device is a facility for PVD coating or for galvanic coating.
- 7. (withdrawn) The production facility as claimed in claim 5, characterized in that the creating device (17) is preceded by a deforming device, in particular a stretching device (23), for the substrate band.
- 8. (withdrawn) The production facility as claimed in claim 5, characterized in that the creating device (17) is preceded by a temperature-controlling device (22) for the substrate band.
 - 9. (withdrawn) The production facility as claimed in claim 5, characterized in that the substrate band (12) is configured as an endless belt circulating in the production facility.
- 10. (withdrawn) The production facility as claimed in claim 6, characterized in that the creating device (17) is preceded by a deforming device, in particular a stretching device (23), for the substrate band.

- 11. (withdrawn) The production facility as claimed in claim 6, characterized in that the creating device (17) is preceded by a temperature-controlling device (22) for the substrate band.
 - 12. (withdrawn) The production facility as claimed in claim 6, characterized in that the substrate band (12) is configured as an endless belt circulating in the production facility.
 - 13. (withdrawn) The production facility as claimed in claim 7, characterized in that the substrate band (12) is configured as an endless belt circulating in the production facility.
 - 14. (withdrawn) The production facility as claimed in claim 8, characterized in that the substrate band (12) is configured as an endless belt circulating in the production facility.